

IN THE CLAIMS:

Please amend claims 1-6 as shown below, in which deleted terms are shown with strikethrough and added terms are shown with underscoring. Also, please add claims 7-8 as shown.

1. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle equipped with a seat, which is supported by a vehicle body through a weight sensor, ~~wherein~~ comprising:
a seatbelt-anchor is fixed to a member, which is positioned ~~near~~ nearer to the seat than the weight sensor.

2. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle according to claim 1, ~~wherein~~ further comprising
a buckle, which is engaged with ~~/~~ and disengaged from a tang of the seatbelt apparatus, is fixed to a another member, which is positioned ~~near~~ nearer to the seat than the weight sensor.

3. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle equipped with a seat, which is provided on a vehicle body through a weight sensor, wherein
the seatbelt apparatus includes:
a buckle adapted to be fixed to one side of the seat ~~of a vehicle~~;
a seatbelt, one end of the seatbelt is adapted to be fixed at the vehicle so that it allows ~~to~~ adjust adjustment of the length of the seatbelt, and the other end of the seatbelt is connected to an anchor that is adapted to be fixed to the other side of the seat; and
a tang, which is provided on the seatbelt and ~~is engaged~~ operatively engages with the buckle so as to hold an occupant to the seat, wherein

the anchor and the buckle are adapted to be fixed at ~~the~~ positions ~~near~~ nearer to the seat than the weight sensor.

4. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle according to claim 3, wherein

the weight sensor includes

a detector which measures a load ~~to be~~ applied to the seat, and

an accommodator which stores the detector at an underside thereof, wherein

the buckle is adapted to be fixed to the accommodator.

5. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle according to claim 4, wherein

the seat has a pair of weight sensors at ~~the~~ both sides thereof, wherein the anchor is adapted to be fixed to the accommodator of the weight sensor, which is located at the outer side with respect to the vehicle body, and the other end of the seatbelt is adapted to be fixed to the accommodator of the weight sensor, which is located at the inner side with respect to the vehicle body.

6. (Currently amended) An attaching structure for a seatbelt apparatus of a vehicle according to claim 5, wherein

the buckle is adapted to be connected to the accommodator through a bracket, which has a mounting part that allows ~~to fix~~ fixation of the bracket to the accommodator from ~~the~~ a rear-

side direction with respect to the seat.

7. (New) An attaching structure for a seatbelt apparatus of a vehicle according to claim 1, wherein said member is a part of the weight sensor which is not affected by a load applied to the seat.

8. (New) The attaching structure for a seatbelt apparatus of a vehicle according to claim 1, wherein

the weight sensor includes

a detector which measures a load applied to the seat, and

an accommodator which stores the detector at an underside thereof, wherein

the accommodator is said member.